

# Main technical parameters and sizes

型号规格 Model specification		YFB-6A/※3-1/16"	YFB-6A/※4-1/16"	YFB-6ALY/※3-1/16" YFB-6ALL/※3-1/16"	YFB-6ALY/※4-1/16" YFB-6ALL/※4-1/16"
通径与压力范围 <sup>(1)</sup> Test range between DN and PN	公称规格 in DN/mm Nominal diameter	2-1/19"~3-1/16"	3-1/19"~4-1/16"	2-1/19"~3-1/16"	3-1/19"~4-1/16"
	公称压力 psi psi Nominal pressure	3000~15000	3000~15000	3000~15000	3000~15000
结构长度范围 Valve face-to-face dimension	最短结构长度 mm The min.valve face- to-face dimension	371	435	371	435
	最长结构长度 mm The max.valve face- to-face dimension	620	737	620	737
法兰直径与厚度范围 Range between flange diameter and thickness	最小法兰直径 / 厚度mm Min.flange diameter/thickness	216 / 46.1	240 / 46.1	216 / 46.1	240 / 46.1
	最大法兰直径 / 厚度mm Max.flange diameter/thickness	270 / 58.4	360 / 78.6	270 / 58.4	360 / 78.6
盲板间距范围 <sup>(2)</sup> Blind flange spacing	最小间距mm Min space between	350	415	350	415
	最大间距mm Max space between	950	1000	800	920
液压系统 Hydraulic system	油泵额定压力MPa Oil pump pressure	6.3			
	排量ml / r Flow	16	25	16	25
	高压 (增压) MPa Boosting	≤ 31.5			
	系统调压范围MPa Pressure adjusting range	≤ 6.3			
电源 Power	电压V/频率Hz Voltage/Frequency	380 / 50			
电机 Motor	功率kW / 极数P Power/Pole	2.2 / 6	3 / 6	2.2 / 6	3 / 6
外形尺寸 <sup>(2)</sup> Overall size	长 mm (L)	2700	3200	2100	2400
	宽 mm (W)	1510	1750	1100	1300
	高 mm (H)	1350	1450	1900	2000
重量/Weight	kg	3000	4400	3000	4000