

Main technical parameters and sizes

型号 Model		YFB-DF /※300	YFB-DF/※ (2)250/500	YFB-DF/※ (2)300/600	YFB-DF/※ (2)300/800	YFB-DF/※ (2)500/1000	YFB-DF/※ (2)600/1200	YFB-DF/※ (2)800/1600	YFB-DF/※ 2000	YFB-DF/※ 2200	YFB-DF/※ 2400	YFB-DF/※ 3000	YFB-DF/※ 3600
规格 ⁽¹⁾ specification		DN 50-300	DN50-250 DN250-500	DN50-300 DN300-600	DN50-300 DN350-800	DN250-500 DN500-1000	DN300-600 DN700-1200	DN350-800 DN900-1600	DN1200 -2000	DN1400 -2200	DN1600 -2400	DN1600 -3000	DN1600 -3600
液压系统 Hydraulic system	油泵额定压力MPa Oil pump pressure	6.3											
	排量ml / r Displacement	16	25	25	25	40	40	40	63	63	63	80	80
	高压（增压）MPa High pressure (Boosting)	≤31.5											
	系统调压范围MPa Pressure adjusting range	≤6.3											
电源 Power	电压V / 频率Hz Voltage / Frequency	380 / 50											
电机 Motor	功率kW / 极数P Power / Pole	2.2 / 6	3 / 6	3 / 6	3 / 6	5.5 / 6	5.5 / 6	5.5 / 6	7.5 / 6	7.5 / 6	7.5 / 6	11 / 6	11 / 6
最小阀门法兰(mm) The min. valve flange		150	150 /395	150 /445	150 /505	395 /670	445 /895	505 /1075	1405	1575	1790	1790	1790
最大阀门法兰(mm) The max. valve flange		485	405 /700	485 /815	485 /1060	700 /1289	815 /1485	1060 /1915	2325	2475	2685	3405	3840
压爪至工作盘最大距离 ⁽²⁾ (mm) The max. distance between claw and work table		370	370 /550	370 /620	370 /637	550 /1100	620 /1225	637 /1225	1225	1250	1250	1250	1250
外形尺寸 ⁽³⁾ Overall size	长L(mm)	2000	3500	3500	3600	4150	4900	5200	4500	5000	5500	8400	10700
	宽W(mm)	1200	1350	1350	1500	1850	2200	2350	2750	3300	3600	6160	8200
	高H(mm)	1850	1980	1980	2050	2050	2050	2200	2200	2200	2200	3065	3100
重量 ≈ (kg) Weight		2000	4500	4500	6000	7500	8000	9800	9000	11500	13000	58000	70000